



Tom Symons, Sales Associate  
Office 570-544-2261 Cell 570-516-7815  
9 Schaeffers Hill Road, Minersville, PA 17954



## BlendCrete

ProSpec® BlendCrete® is a fast-setting, one component, polymer modified, calcium aluminate cement-based concrete and masonry patching compound designed for horizontal, vertical and overhead repair applications.

### Features and Benefits

- Interior/exterior  
Horizontal, vertical and overhead repair applications
  - Apply to 1/4" - 2" (6 mm - 51 mm)\*
  - Fast setting, low slump repair mortar that can be troweled, shaped and shaved after taking an initial set
  - Easy shaping and molding
  - One component incorporating a water activated polymer system
  - Integrated corrosion inhibitor
  - Tenacious bond to substrates
  - Normal set time of approximately 30 minutes
  - Available in 15 minute set time formula
- \* Use TEC® Patch Additive (used at full strength) for thicknesses of 1/4" (6 mm) to 1/2" (13 mm).
- Used interior or exterior, above or below grade, on horizontal, vertical and overhead
  - Suited for patching distressed surfaces including precast products, concrete pipe, curbs, sidewalks, bridges, panels and walls
  - Used to fill honeycombs, formed high rise holes, spalls or irregularities due to misaligned forms or unconsolidated concrete